

DL6790-LOC1

Digital/LED Voltage & Continuity Tester with Lockout Kit

The Di-LOG DL6780-LOC1 CombiVolt 1 LED Tester packaged with our DLLOC1 Personal Lockout Kit offers a simple cost effective voltage indication kit with our entry level kit for locking out most MCBs.

Features

- Meets safety and performance requirements of BS EN 61243-3 2014
- Continuity testing with optical and acoustic indication
- Automatic switching between voltage and continuity
- CAT IV 600V Safety Rated
- Phase rotation test system
- Single pole phase indication
- Fully compliant with GS38
- Fully operational voltage indication even when batteries are discharged
- Key'd to differ padlock
- Pins out and universal lockout devices with tag

DL6790 Voltage Indicator Specification	
2 Pole Voltage Indication	
Voltage range	12 - 690V AC/DC
LED resolution	12, 24,50, 120, 230, 400 & 690V
Voltage detection	Automatic
Frequency range	0 - 400Hz
Peak current	3.5mA
Operation time	30 Seconds
Acoustic AC/DC signal	✓
Auto power on	<12V AC/DC
IP rating	IP65
Single Pole Indication	
Voltage range	100 - 690V AC
Frequency range	50 - 400Hz
Continuity	
Measurement range	0 - 400kΩ
Phase Rotation Test	
Voltage range	100 - 690V AC
Frequency	45 - 65Hz
Over voltage protection	690V AC/DC
Other Information	
Dimensions	225mm x 70mm x 28mm
Weight (net)	200g
Power supply	2 x 1.5V (RO3) AAA (supplied)
EAN	5060082543555



EMC & LVD
EN 61326-1
EN 61243-3:2014
EN 61010-1
EN 61010-2-030
EN 61010-031
EN 60529 (IP65)

support@dilog.co.uk

Di-LOG Ltd
Unit 28 Wheel Forge Way
Trafford Park
Manchester M17 1EH
UK
Tel: +44 (0)161 877 0322
Email: sales@dilog.co.uk
Website: www.dilog.co.uk