

Di-LOG
...measurably better

DL9062 - Earth Resistance Tester



The DL9062 is a hand Earth Resistance Tester c/w Zero option for adjustment

The DL9062 has a large back lit LCD display, with a measuring range up to 2KΩ. With the kit including 2 measurement stakes and 4 test cables, the DL9062 provides a cost effective way of ERT testing.

The double moulded case makes the instrument suitable for the most rugged applications.

Key Features

- Earth Resistance from 20Ω to 2000Ω
- Earth Voltage to 200V
- Continuity Test 0.1kΩ to 200kΩ
- Back lit display
- Test Hold for easy operation
- CAT III 1000V
- Zero auto adjustment
- Auto Power Off

Di-LOG
GROUP

**Sales Freephone
0800 018 9112**

**Email
sales@dilog.co.uk**

www.dilog.co.uk

DL9062 - SPECIFICATIONS

Continuity Ohms

Range	Resolution	Accuracy
200k Ω	0.1k Ω	± 1 % of rdg ± 2 dgts

Max open circuit voltage:- 4.5V

Overload protection:- 250Vrms

Earth Voltage

Range	Resolution	Accuracy
200V	0.1V	± 3 % of rdg ± 3 dgts

Voltage DC (Auto-ranging)

Range	Resolution	Accuracy
1000V	1V	± 0.8 % of rdg ± 3 dgts

Input Impedance:- 10M Ω

Overload protection:- 1000V rms

AC Voltage (Auto-ranging)

Range	Resolution	Accuracy
750V	1V	± 1.2 % of rdg ± 10 dgts

Input Impedance:- 10M Ω

Overload Protection:- 750Vrms

Earth Resistance

Range	Resolution	Resolution	Accuracy
20 Ω	0.01-20.00 Ω	0.01 Ω	± 2 % of rdg ± 10 dgts
200 Ω	0.1-200.1 Ω	0.1 Ω	± 2 % of rdg ± 3 dgts
2000 Ω	1-2000 Ω	1 Ω	± 2 % of rdg ± 3 dgts



Information

Supplied with 6 x 1.5V AA, Carry Case, 2 x Earth Spikes, 3 x Cable 5M, Leads and Bulldog Clips

Dimensions: 200(H) x 92(W) x 50(D) mm

Weight: 582g

**All Di-log 17th Edition
supported by a
2 Year Warranty**

CE EMC & LVD
EN:61326, 61010-1 CAT III 1000V, 61010-02-031

Di-log Test Equipment
Unit 28 Wheel Forge Way
Trafford Park
Manchester
M17 1EH

Sales: (0161) 877 0322
Fax: (0161) 877 1614
Email: sales@dilog.co.uk