

Di-LOG
...measurably better

DL6505 - AC Mini Clamp Meter



The DL6518 has an accurate measurement of earth leakage down to a resolution of 10uA, enabling the detection of nuisance tripping caused by faulty appliances or circuit faults resulting in current leakage to earth.



Key Features:

- 10uA resolution
- 200A AC Current Measurement
- Hold/Max Function
- Supplied with Carry Pouch
- Auto Power Off

Di-LOG
GROUP

Sales Freephone
0800 018 9112

Email
sales@dilog.co.uk

www.dilog.co.uk

SPECIFICATIONS

AC Current - DL6518

Range	Resolution	Accuracy 50/60 Hz	40Hz-1kHz
0 - 200mA	100uA	$\pm 1.5\%$ rdg + 3dgts	$\pm 2.5\%$ rdg + 8 dgts
0 - 2A	1mA	$\pm 1.5\%$ rdg + 3dgts	$\pm 2.5\%$ rdg + 8 dgts
0 - 200A	100mA	$\pm 1.5\%$ rdg + 3dgts	$\pm 2.5\%$ rdg + 8 dgts

**All Di-log Clampmeters
supported by a
2 Year Warranty**

Miscellaneous

Supplied with 2x 1.5V AAA battery
Dimensions: 182(H) x 61(W) x 34(D) mm
Weight: 225g Includes batteries
Jaw opening:- 30mm

CE

EMC & LVD
EN: 50081-1, 50082-1
EN: 61010-1, EN 61010-02-031

Di-log Test Equipment
Unit 28 Wheel Forge Way
Trafford Park
Manchester
M17 1EH

Sales: (0161) 877 0322
Fax: (0161) 877 1614
Email: sales@dilog.co.uk