

DL7203 - Lamp Tester



The DL7203 is a handy test instrument for swift fault finding in all gasfilled low pressure and high pressure discharge lamps and fluorescent tubes.

The DL7203 safely tests fluorescent lamps, the test is carried out without disassembling the lamp from the fitting which can be tested in-situ.

Key Features

- Tests Fluorescent Tubes
- High/Low Pressure Sodium
- Neon & Mercury Vapour
- Metal Halogen
- Integrated Single Pole Voltage Tester
- Optical and Acoustic display for Voltage and Continuity

Di-LOG

Sales Freephone 0800 018 9112 Email sales@dilog.co.uk

www.dilog.co.uk

DL7203 - SPECIFICATIONS

Specifications

Range	Resolution
Live conductor Indication	60-250V AC, 40-60Hz
Continuity Varification	0.5MΩ (test current <7μA)
Lamp Tester Voltage	3kV / 160kHz (Test current 2007μA)
Measure Category	CAT II 250V

Supplied with 1 x 9v battery

Dimensions: 189H) x 26.5(W) x 50(D) mm

Weight: 60g

All Di-log Lamp Testers supported by a 2 Year Warranty



In conformance with CE safety standard, CAT II 250V

Di-log Test Equipment Unit 28 Wheel Forge Way Trafford Park Manchester M17 1EH

Sales: (0161) 877 0322 Fax: (0161) 877 1614 Email: sales@dilog.co.uk