

Di-LOG
...measurably better

DL9206 - Compact Multimeter



The DL9206 is a hand held compact Digital Multimeter, enclosed in a double moulded, rugged enclosure making it a versatile instrument suitable for the most demanding application.

The DL9206 measures up to 1000V, AC/DC voltage, 10A Current, Capacitance and Temperature measurement, provides maximum versatility for both the electrical and maintenance industry. The DL9206 a must have tool for the electrical engineer.



Key Features

- Voltage range up to 1kV AC, 600V DC
- Resistance measurement to 60MΩ
- DC current to 10A
- Min/Max and Hold Function
- K-type Thermocouple adaptor
- Capacitance measurement to 4000μF
- Auto Power Off
-

Di-LOG
GROUP

Sales Freephone
0800 018 9112
Email
sales@dilog.co.uk

www.dilog.co.uk

SPECIFICATIONS

DC Voltage

Range	Resolution	Accuracy
600.0mV	0.1mV	±0.5 % of rdg ± 2 dgts
6.000V	1mV	±1.2 % of rdg ± 2 dgts
60.00V	10mV	±1.2 % of rdg ± 2 dgts
600.0V	100mV	±1.2 % of rdg ± 2 dgts
1000V	1V	±1.5 % of rdg ± 2 dgts

Input Impedance: 7.8MΩ.

Maximum Input: 1000V DC or 750V AC rms.

AC Voltage

Range	Resolution	Accuracy
6.000V	1mV	±1.2 % of rdg ± 3 dgts
60.00V	10mV	±1.5 % of rdg ± 3 dgts
600.0V	100mV	±1.5 % of rdg ± 3 dgts
750V	1V	±2.0 % of rdg ± 4 dgts

Input Impedance: 7.8MΩ.

Frequency Range: 50 to 60Hz

Maximum Input: 1000V DC or 750V AC rms.

DC Current (Auto-ranging for mA)

Range	Resolution	Accuracy
10A	1mA	±2.5 % of rdg ± 5 dgts

Overload Protection: 10A / 250V Fuse.

Maximum Input: 10A DC or AC rms on 10A DC range (30 second max every 15 minutes)

AC Current (Auto-ranging for mA)

Range	Resolution	Accuracy
10A	10mA	±3.0 % of rdg ± 7 dgts

Overload Protection: 10A / 250V Fuse.

Frequency Range: 50 to 60 Hz.

Maximum Input: 10A DC or AC rms on 10A AC range (30 second max every 15 minutes)

Resistance

Range	Resolution	Accuracy
600.0Ω	0.1Ω	±1.2 % of rdg ± 4 dgts
6.000kΩ	1Ω	±1.0 % of rdg ± 2 dgts
60.00kΩ	10Ω	±1.2 % of rdg ± 2 dgts
600.0kΩ	100Ω	±1.2 % of rdg ± 2 dgts
6.000MΩ	1kΩ	±1.2 % of rdg ± 2 dgts
60.00MΩ	10kΩ	±2.0 % of rdg ± 3 dgts

Input Protection: 250V DC or 250V AC rms.

Range	Resolution	Accuracy
40.00nF	10pF	±5.0 % of rdg ± 7 dgts
400.0nF	0.1nF	±3.0 % of rdg ± 5 dgts
4.000uF	1nF	±3.0 % of rdg ± 5 dgts
40.00uF	10nF	±3.0 % of rdg ± 5 dgts
400.0uF	0.1uF	±5.0 % of rdg ± 5 dgts
4000uF	1uF	±5.0 % of rdg ± 5 dgts

Input Protection: 250V DC or 250V AC rms.

Frequency (Auto-ranging)

Range	Resolution	Accuracy
6.999Hz	0.001Hz	
69.99Hz	0.01Hz	±1.5 % of rdg ± 5 dgts
699.9Hz	0.1Hz	±1.2 % of rdg ± 3 dgts
6.999kHz	1Hz	±1.2 % of rdg ± 3 dgts
69.99kHz	10Hz	±1.2 % of rdg ± 3 dgts
699.9kHz	100Hz	±1.2 % of rdg ± 3 dgts
2.999Mhz	1kHz	±1.5 % of rdg ± 4 dgts

Sensitivity: >0.5V RMS while <1Mhz

Sensitivity: >3V RMS while > 1Mhz

Overload Protection: 250V DC or AC rms

Duty Cycle

Range	Resolution	Accuracy
0.1% - 99.9%	0.1%	±1.2 % of rdg ± 2 dgts

Pulse Width: >100us, <100ms

Frequency Width: 5Hz - 150kHz

Sensitivity: >0.5V RMS

Overload Protection: 250V DC or AC rms

Range	Resolution	Accuracy
-20°C - 760°C	1°C	±3% of rdg ± 5 dgts
-4°F - 1400°F	1°F	±3% of rdg ± 5 dgts

Sensor: Type K Thermocouple

Overload Protection: 250V DC or AC rms

Diode Test

Test current: 0.3mA typical

Open circuit voltage: 1.5V dc typical

Overload protection: 250V DC or AC rms.

Audible continuity

Audible threshold: Less than 30Ω;

Test current: <0.3mA

Overload protection: 250V DC or AC rms.

Miscellaneous

Supplied with 1x 9V battery

Dimensions: 150(H) x 70(W) x 48(D) mm

Weight: 255g

**All Di-log Multimeters
supported by a
2 Year Warranty**

C

EMC & LVD

EN: 50081-1, 50082-1

EN: 61010-1, EN 61010-02-031

Di-log Test Equipment
Unit 28 Wheel Forge Way
Trafford Park
Manchester
M17 1EH

Sales: (0161) 877 0322

Fax: (0161) 877 1614

Email: sales@dilog.co.uk