

LS50M

50 Metre R2 Wander Test Lead

The Di-LOG LS50M R2 Wander Lead is a professional-grade test reel designed for efficient and accurate R2 continuity and main earth bonding testing. Engineered for durability and ease of use, it enables electricians to quickly verify the continuity of circuit protective conductors (CPCs) across large installations.

Key Applications

- R2 continuity testing of final circuits
- Verification of circuit protective conductors (CPC)
- Main and supplementary earth bonding checks
- Electrical installation inspection and testing (EIC / EICR)
- Ideal for domestic, commercial, and industrial environments

Features

- **Dual Drum Technology:** Enables smooth, even cable distribution across the reel, improving winding efficiency and reducing cable stress.
- **Anti-Tangle Cable Guide:** Prevents snagging and twisting during deployment and retrieval, ensuring consistent performance on-site.
- **Heavy-Duty Construction:** Built to withstand demanding environments, offering long-term reliability for daily professional use.
- **Extended Reach Capability:** 50m cable length allows for testing across large circuits without repositioning equipment.

Specifications

LS50M	
Colour	Green
Safety Rating	Croc Clip CAT III 1000V
Insulation	Double
Cable Length	50M
Application	R2 Continuity & Earth Bond Testing
Cable	High-flex, durable test lead
Cable Management	Manual, high-efficiency dual drum winding
Compatibility	Most Multifunction Testers (MFT) and Insulation & Continuity Testers

